

Wall luminaires

with light emission on one or two sides

A series of wall mounted luminaires with light emission in one or two directions. Thick-walled crystal glass characterizes the design of these distinctive luminaires. Arranged individually or in groups, they are great design elements for a host of lighting applications.

BEGA 19 538 small opening wiring box (included) required for proper installation.



Die-cast aluminum · Crystal glass inside white

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com



All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 64



Light emission on **one side**

	LED	A	B	C	Required wiring box
33 405	3.9 W	3 1/2	4 1/4	4 1/4	19 538
33 449	8.2 W	4 3/4	5 1/2	5 1/2	-



Light emission on **two sides**

	LED	A	B	C	Required wiring box
33 505	5.8 W	3 1/2	4 3/4	4 1/4	19 538
33 549	16.4 W	4 3/4	5 7/8	5 1/2	-