



Wall luminaires
with directed light

A series of wall mounted luminaires with directed light. At low mounting heights they can be used for marking dangerous areas such as steps, or arrange them in rows to illuminate corridors and passageways. At high mounting heights they can be used near doors or to accent architecture.

BEGA 19 538 small opening wiring box (included) required for proper installation.



Die-cast aluminum · Matte safety glass

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 64



Wall luminaires		LED	A	B	C	Required wiring box
22 215	ADA	3.0 W	3 1/2"	3 3/4"	2 3/8"	19 538
22 261	ADA	4.2 W	6 7/8"	3 3/4"	2 3/8"	-

