



Wall washers
with light emission on two sides

A series of wall mounted luminaires with symmetric, asymmetric, or lateral throw light distribution on two sides. Light distribution in the upward direction is always symmetric. Symmetric light distribution is used to illuminate facade and wall surfaces, with the installation surface also acting as the reflection surface. Asymmetric light distribution illuminates ceiling or ground surfaces in front of the mounting surface. Lateral throw light distribution illuminates ground surfaces along walls.


Die-cast aluminum · Safety glass · Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Symmetric upwards · Symmetric downwards

	LED	A	B	C
33 395	25.3 W	9 3/4"	6 1/4"	7 3/4"
33 389	43.0 W	12 7/8"	7 1/8"	10 1/2"



Symmetric upwards · Asymmetric downwards

	LED	A	B	C
33 394	25.3 W	9 3/4"	6 1/4"	7 3/4"
33 387	43.0 W	12 7/8"	7 1/8"	10 1/2"



Symmetric upwards · Lateral throw downwards

	LED	A	B	C
33 393	25.3 W	9 3/4"	6 1/4"	7 3/4"
33 379	43.0 W	12 7/8"	7 1/8"	10 1/2"