



Wall luminaires
with directed light

Wall mounted luminaires with symmetric or asymmetric light distribution. This group of luminaires is designed for general illumination of pathways, walkways and plazas.


Die-cast aluminum · Clear or white safety glass · Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65



Symmetric light distribution

	LED	A	B	C
24 218	8.9 W	8	8	3 3/4
33 242	14.9 W	8	8	3 3/4
24 219	14.9 W	11 1/2	11 1/2	7 5/8
33 243	29.8 W	11 1/2	11 1/2	5 3/8



Asymmetric light distribution

	LED	A	B	C
24 220	8.9 W	8	8	6 1/2
33 238	17.8 W	8	8	6 1/2
24 221	14.9 W	11 1/2	11 1/2	7 7/8
33 239	29.8 W	11 1/2	11 1/2	7 7/8