



Wall luminaires
with light emissions on one or two sides

A series of wall mounted luminaires with light emission on one or two sides. The narrow beam light distribution of the luminaires is identical in both directions. Arranged individually or in groups, they are great design elements for a host of lighting applications.

BEGA 19 537 small opening wiring box (included) required for proper installation.

Die-cast aluminum · Safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Light emission on **one-side**

	LED	β	A	B	C	D	Required wiring box
66 655	7.9 W	21°	4 3/8"	9 1/8"	6 1/4"	1 1/2"	19 537
24 034	12.1 W	17°	4 3/8"	9 1/8"	6 1/4"	1 1/2"	19 537
66 698	12.5 W	18°	5 7/8"	11"	7 3/4"	1 1/2"	19 537
24 035	18.1 W	15°	5 7/8"	11"	7 3/4"	1 1/2"	19 537



Light emission on **two-sides**

	LED	β	A	B	C	D	Required wiring box
66 516	15.8 W	21°	4 3/8"	9 1/8"	6 1/4"	1 1/2"	19 537
24 008	24.2 W	18°	4 3/8"	9 1/8"	6 1/4"	1 1/2"	19 537
66 519	25.0 W	17°	5 7/8"	11"	7 3/4"	1 1/2"	19 537
24 009	36.2 W	13°	5 7/8"	11"	7 3/4"	1 1/2"	19 537

β = Beam angle