



### Wall luminaires

A series of wall luminaires with shielded light distribution. The shape of the lantern is unmatched in its diversity. These luminaires are particularly suitable for illuminating areas directly below the mounting surface such as courtyards or alongside and above doors.


Copper · Three-ply opal glass

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

Natural copper. Time and weather factors will create the natural patina of copper.


NRTL listed to North American standards  
Suitable for wet locations · Protection class IP 44



Wall luminaires					
	LED	A	B	C	D
<b>31171</b>	3.9 W	9 1/4	8 1/8	14 1/2	4 3/8



Wall luminaires					
	LED	A	B	C	D
<b>31058</b>	3.0 W	7 1/8	6 1/2	7 3/4	3 3/8
<b>31060</b>	3.9 W	10 1/4	8	11	4 3/8



Wall luminaires					
	LED	A	B	C	D
<b>31004</b>	4.2 W	7 1/8	9 1/2	12 1/2	3 3/8
<b>31008</b>	3.9 W	10 1/4	11 3/4	16 3/8	4 3/8