



For matching wall luminaires, see Page 54.



Asymmetric flat beam light distribution



On-ground luminaires

Extended throw

Ground mounted bollard luminaire with low mounting height. The specially designed optics in this luminaire family allow for superior illumination of ground surfaces at an extremely low mounting height.


Die-cast and extruded aluminum · Safety glass with optical texture
Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



On-ground luminaire · extended throw					Anchorage
LED	A	B	C	D	
84 081	12.2 W	13%	14%	3 1/2	79 825



Asymmetric light distribution



On-ground surface washer

A series of ground mounted luminaires for illuminating horizontal surfaces from very low mounting heights. These luminaires are ideally suited for providing spatial illumination in squares, entrances and wide pathways in private and public areas. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.


Die-cast aluminum · Safety glass · Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 67



On-ground luminaires · surface washer			
LED	A	B	C
77 791	8.4 W	9	6 3/4 7 1/8
84 815	16.4 W	9	6 3/4 7 1/8

