

Light emission 180°

Light emission 360°

Shielded bollards

with 180° or 360° light distribution

A series of bollards with shielded 180° or 360° light distribution. This luminaire family is designed to provide rotationally symmetric or one sided illumination of ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.


Die-cast and extruded aluminum · Clear safety glass
Reflector made of pure anodized aluminum

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Bollards · 180°				
	LED	A	B	Anchorage
77 752	5.4 W	6 1/2"	8 5/8"	79 817
77 787	6.2 W	11 7/8"	19 3/4"	79 818
77 753	5.4 W	6 1/2"	39 1/4"	79 817

Bollards · 360°				
	LED	A	B	Anchorage
99 577	14.4 W	6 1/2"	8 5/8"	79 817
99 578	12.4 W	11 7/8"	19 3/4"	79 818
99 570	14.4 W	6 1/2"	39 1/4"	79 817

