

Light emission 360°

### Shielded bollards

A series of bollard luminaires with fully shielded light output. The glare-free illumination of these luminaires is ideally suited for lighting entrances and footpaths as well as many areas of garden and landscape architecture. Designed for use in the illumination of gardens and residential installations.


Die-cast and extruded aluminum · Clear safety glass  
Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com)

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations  
Protection class IP 65



Shielded bollards					Anchorage
	LED	A	B	C	
<b>88 262</b>	20.6 W	9%	21%	4%	<b>79 824</b>
<b>88 261</b>	20.6 W	9%	37%	4%	<b>79 824</b>

