

Unshielded bollards
with light emission on one or two sides

A series of bollard luminaires with unshielded light distribution on one or two sides. The unshielded light is ideally suited for the illumination of footpaths, entrance areas or in garden and residential areas. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.


Die-cast and extruded aluminum · White safety glass

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Light emission on one side						
	LED	A	B	C	D	Anchorage
99 326	11.4 W	4 ¾"	39 ¾"	3 1/8"	6 ¾"	79 817

Light emission on two sides						
	LED	A	B	C	D	Anchorage
99 330	22.8 W	4 ¾"	39 ¾"	3 1/8"	6 ¾"	79 817

