



Unshielded bollards

Bollards with diffuse 180° or 360° light distribution featuring three-ply opal glass and safety guard. Designed for effective lighting of gardens and residential applications.

Die-cast and extruded aluminum · Three ply opal glass

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Light emission 180° · with safety guard				
	LED	A	B	Anchorage
84 024	3.9 W	4%	28 3/4"	79 824
84 025	8.2 W	5 1/2%	35 3/4"	79 817

Light emission 360° · with safety guard				
	LED	A	B	Anchorage
84 028	3.9 W	4%	28 3/4"	79 824
84 029	8.2 W	5 1/2%	35 3/4"	79 817

Light emission 360° · unshielded				
	LED	A	B	Anchorage
77 742	6.3 W	4%	28 3/4"	79 824
77 743	10.5 W	5 1/2%	35 3/4"	79 817



Light emission 180°
With safety guard

Light emission 360°
With safety guard

Light emission 360°
Unshielded