



Pole-top luminaires
with asymmetric light distribution

A series of pole-top luminaires with asymmetric light distribution. These luminaires are designed to illuminate roadways, squares, driveways and pedestrian areas.

Die-cast and extruded aluminum · Clear acrylic diffuser with optical texture
Reflector made of pure anodized aluminum

LED color temperatures: 2700K, 3000K, 3500K, 4000K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations · Protection class IP 65



Available in twin configuration as custom product.



Pole-top luminaires				
	LED	A	B	C
77 910	15.4 W	19 3/4"	40 5/8"	32 1/2"
77 911	23.2 W	26 5/8"	46 1/4"	40 1/2"

Poles for above luminaires – see page 406 - 411.

