



For pendant luminaires, see Page 76.

Catenary luminaires
with symmetric light distribution

A series of pendant luminaires for catenary suspension systems with shielded light or symmetric wide spread light distribution. The cable hanger system is suitable for transverse suspension systems and longitudinal chain systems. The luminaires are designed specifically to illuminate plazas, passageways and pedestrian zones. The symmetric wide spread light distribution luminaire features clear acrylic diffuser that spreads the light and creates visual interest.


Die-cast aluminum · Clear safety glass or clear acrylic diffuser
Reflector made of pure anodized aluminum
Cable hanger made of stainless steel

LED color temperatures: 2700K, 3000K, 3500K, 4000K


BEGA luminaires offer a minimum service life of 60,000 hours, with suitable LED replacement modules guaranteed for up to 20 years after date of purchase. Further LED technical data including luminous flux, CRI, dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White, as well as optionally available RAL and custom colors, are a polyester powder.

NRTL listed to North American standards · Suitable for wet locations
Protection class IP 65



Catenary luminaires · shielded				
	LED	A	B	C
84 405	35.7 W	7 1/2	19 1/8	20 3/4



Catenary luminaires · clear acrylic				
	LED	A	B	C
84 406	35.7 W	7 1/2	40 3/4	42 1/4