



Ceiling luminaires · Downlights

Direct and indirect light distribution

LED downlights with directed and diffuse light distributions, available in three sizes and three exterior finishes. Light is directed downward by a precise reflector, while additional high angle light illuminates the opal glass accent. The dual light distribution results in an efficient ceiling luminaire with a high degree of visual comfort. Provided with electronic driver.

Hand-blown, three-ply opal glass, satin matte finish with screw neck  
Molded silicone lens · Reflector made of pure anodized aluminum  
Die-cast aluminum housing

Select the desired exterior finish by using appropriate code number as suffix

- White Code number .1
- Stainless steel Code number .2
- Velvet black Code number .5

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at [www.bega-us.com](http://www.bega-us.com).

NRTL listed to North American Standards, interior use only  
Refer to page 185 for more information



Select the desired exterior finish by using appropriate code number as suffix.



White  
Code number .1



Stainless steel  
Code number .2



Velvet black  
Code number .5



Downlight				
	LED	β	A	B
50 517	8.1 W	42°	4 3/4	6 1/2
50 519	11.5 W	42°	5 3/8	7 1/4
50 521	17.0 W	43°	7	9

β = Beam angle