

Application

Designed for low mounting heights for interior and exterior locations, the wide spread light distribution is suitable for illuminating corridors and pathways.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Clear safety glass with optical texture
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 5.7 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	17.9 W
System wattage	22 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1678 lumens (300K)
Lifetime at Ta = 15° C	>500,000 h (L70)
Lifetime at Ta = 45° C	120,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:

BEGA Product:


Project:

Modified:

Available Accessories

19524 Concrete protection cover

See individual accessory spec sheet for details.



LED recessed wall · wide spread				
	LED	A	B	C
22354 ADA	17.9 W	9 7⁄8	9 7⁄8	5 3⁄8

