

Application

This LED wall mounted luminaire has light output in two directions. Arranged individually or in groups, it is a great design element for a host of lighting applications.

Materials

Luminaire housing and constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Matte safety glass  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 3.1 lbs

Electrical

Operating voltage 120-277V AC  
Minimum start temperature -20° C  
LED module wattage 7.7 W  
System wattage 10 W  
Controllability 0-10V dimmable  
Color rendering index Ra > 80  
Luminaire lumens 704 lumens (3000K)  
LED service life (L70) 60,000 hours

LED color temperature

4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**  
Amber - Product number + **AMB**

Wildlife friendly amber LED - Optional

Luminaire is optionally available with a narrow bandwidth, amber LED source (585-600nm) approved by the FWC. This light output is suggested for use within close proximity to sea turtle nesting and hatching habitats. Electrical and control information may vary from standard luminaire.


LED module wattage 6.0 W (Amber)  
System wattage 10.1 W (Amber)  
Luminaire lumens 184 lumens (Amber)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors    Black (BLK)            White (WHT)            RAL:  
                              Bronze (BRZ)            Silver (SLV)            CUS:



LED wall luminaire · light output on two sides				
	LED	A	B	C
22363	ADA 7.7 W	8 1/2	4 3/8	4

Type:  
BEGA Product:  
Project:  
Modified:

