


BEGA

Photometric Filename: 22363.IES

TEST: BE_22363
TEST LAB: BEGA
DATE: 2/28/2017
LUMINAIRE: 22 363
LAMP: 7.7W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	704
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	70
Total Luminaire Watts	10
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.16 ft
Luminous Width (90-270)	0.56 ft
Luminous Height	0.00 ft

Zonal Lumen Summary

Zone	Lumens
0-10	21.38
10-20	60.68
20-30	84.68
30-40	87.05
40-50	71.02
50-60	43.94
60-70	20.58
70-80	6.41
80-90	0.51
90-100	1.79
100-110	9.10
110-120	20.15
120-130	35.61
130-140	53.36
140-150	64.93
150-160	62.65
160-170	44.10
170-180	15.65



Wall mount - Isofootcandle grid on floor
Mounting Height = 5 ft. Grid Spacing = 5 ft.



Wall mount - Isofootcandle grid on wall
Grid Spacing = 2.5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.


BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2019

3/12/2019

BEGA

Photometric Filename: 22363AMB.IES

TEST: L021905803
 TEST LAB: LIGHT LABORATORY, INC.
 DATE: 3/4/2019
 LUMINAIRE: 22 363 Amber
 LAMP: 6.0W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	184
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	18
Total Luminaire Watts	10.1
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	0.18 ft
Luminous Width (90-270)	0.58 ft
Luminous Height	0.33 ft

Zonal Lumen Summary

Zone	Lumens
0-10	4.91
10-20	14.02
20-30	20.06
30-40	21.10
40-50	17.14
50-60	10.82
60-70	5.35
70-80	1.80
80-90	0.24
90-100	0.65
100-110	2.89
110-120	6.17
120-130	10.41
130-140	15.16
140-150	18.39
150-160	17.79
160-170	12.67
170-180	4.46



Wall mount - Isofootcandle grid on floor
 Mounting Height = 5 ft. Grid Spacing = 2.5 ft.



Wall mount - Isofootcandle grid on wall
 Grid Spacing = 2.5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.