

Application

This LED wall mounted luminaire has light output in two directions. Arranged individually or in groups, it is a great design element for a host of lighting applications.

Materials

Luminaire housing and constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Matte safety glass
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 4.2lbs

Electrical

Operating voltage 120-277VAC
Minimum start temperature -20° C
LED module wattage 15.4 W
System wattage 20.5 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 1663 lumens (3000K)
LED service life (L70) 60,000 hours

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**
Amber - Product number + **AMB**

Wildlife friendly amber LED - Optional

Luminaire is optionally available with a narrow bandwidth, amber LED source (585-600nm) approved by the FWC. This light output is suggested for use within close proximity to sea turtle nesting and hatching habitats. Electrical and control information may vary from standard luminaire.


LED module wattage 12.0 W (Amber)
System wattage 15.7 W (Amber)
Luminaire lumens 344 lumens (Amber)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) White (WHT) RAL:
 Bronze (BRZ) Silver (SLV) CUS:



LED wall luminaire · light output on two sides				
	LED	A	B	C
22 365	ADA 15.4 W	12 ½	4 ¾	4

Type:
BEGA Product:
Project:
Modified:

