

Application

The shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Clear safety glass with optical texture
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Painted aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 3.1 lbs

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 11.8 W
System wattage 14 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 972 lumens (3000K)
Lifetime at Ta = 25° C 50,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:
BEGA Product:
Project:
Modified:

Available Accessories
19523 Concrete protection cover
See individual accessory spec sheet for details.



LED recessed wall · shielded					
		LED	A	B	C
22371	ADA	11.8W	9 7⁄8	4 7⁄8	2

