

Application

The material thickness and strong crystal glass makes this impact-resistant LED luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (\leq 0.3% copper content) A360.0 aluminum alloy
 Heavy pressed crystal glass with optical texture
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP65
 Weight: 2.9lbs

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30°C
 LED module wattage 3.9W
 System wattage 6W
 Controllability 0-10V dimmable
 Color rendering index $Ra > 80$
 Luminaire lumens 395 lumens (3000K)
 Lifetime at $T_a = 15^{\circ}\text{C}$ $>500,000$ h (L70)
 Lifetime at $T_a = 55^{\circ}\text{C}$ 178,000 h (L70)

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED ceiling and wall luminaire · unshielded

	LED	A	B	C
22450 <small>ADA</small>	3.9W	4 3/4	8 1/4	3 1/4



Type:
 BEGA Product:
 Project:
 Modified: