

Application

Interior LED ceiling and wall luminaires with shallow profile designed for general purpose illumination featuring hand-blown, three-ply opal glass with satin matte finish.

Materials

Luminaire housing constructed of aluminum alloy with painted white finish  
Three-ply opal glass

NRTL listed to North American Standards, suitable for damp locations  
Weight: 4.9lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	8.1 W
System wattage	10.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	812 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 45° C	161,000 h (L70)

LED color temperature


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White painted finish

Type:  
BEGA Product:  
Project:  
Modified:



LED ceiling and wall luminaires					
		LED	A	B	C
23 296	ADA	8.1 W	13 3⁄4	3 3⁄8	9 1⁄2

