

Application

LED ceiling and wall luminaires designed for the illumination of rooms, bathrooms, stairways, and other interior spaces characterized by their shallow projection featuring hand-blown, three-ply opal glass with satin matte finish.

Materials

Luminaire housing constructed of aluminum alloy with painted white finish
 Three-ply opal glass satin matte finish
 Optionally available with synthetic diffuser for impact protection, specify luminaire with 'P' suffix

NRTL listed to North American Standards, suitable for damp locations
 Weight: 11.5lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	37.8 W
System wattage	43.5 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	3,636 lumens (3000K)
Lifetime at Ta = 15° C	356,000 h (L70)
Lifetime at Ta = 45° C	62,000 h (L70)


LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White painted finish



LED ceiling and wall luminaire

	LED	A	B	C
23 297 ADA	37.8 W	18 1/2	3 3/4	14 1/4

