

**Application**

LED ceiling and wall luminaire with hand-blown, three-ply opal glass. This family of luminaires can be utilized individually or in groups for glare free illumination of interior and exterior spaces.

**Materials**

Luminaire housing and faceplate constructed of marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Three-ply opal glass satin matte finish  
 High temperature silicone gasket

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65  
 Weight: 8.4 lbs

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	28.1 W
System wattage	32.0 W
Controllability	0-10V dimmable
Color rendering index	R > 90
Luminaire lumens	3,178 lumens (3000K)
Lifetime at Ta = 15° C	372,000 h (L70)
Lifetime at Ta = 30° C	149,000 h (L70)

**LED color temperature**

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED ceiling and wall luminaire			
	LED	A	B
<b>24027</b>	<b>ADA</b> 28.1 W	14 1/4	3 7/8

Type:  
 BEGA Product:  
 Project:  
 Modified:

