

Application

LED wall luminaires with directed narrow beam light distribution on one side that can be oriented upward or downward. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Clear safety glass
Reflector made of pure anodized aluminum
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 4.4 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	12.1 W
System wattage	14.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1,106 lumens (3000K)
Lifetime at Ta = 15° C	380,000 h (L70)
Lifetime at Ta = 40° C	230,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:

BEGA Product:


Project:

Modified:

Available Accessories

79547 Surface mounted wiring box

See individual accessory spec sheet for details.



LED wall luminaire - one-sided light output							Required wiring box
	LED	β	A	B	C	D	
24034	12.1 W	18°	4 ³ / ₈	9	6 ³ / ₈	1 ⁵ / ₈	19537

β = Beam angle

