

Application

LED wall luminaires with symmetrical light distribution designed for general illumination of pathways, plazas and building entrances.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Matte safety glass  
Reflector made of pure anodized aluminum  
Silicone applied robotically to casting, plasma treated for increased adhesion  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP65  
Weight: 8.2 lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	14.9 W
System wattage	17.4 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1,706 lumens (3000K)
Lifetime at Ta = 15° C	185,000 h (L70)
Lifetime at Ta = 50° C	155,000 h (L70)

LED color temperature


4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED wall luminaire · symmetrical light distribution				
	LED	A	B	C
24 219	14.9 W	11	11	5 5/8

Type:

BEGA Product:

Project:

Modified:

