

Application
LED ceiling and wall luminaires with hand-blown, three-ply opal glass. This luminaire can be utilized individually or in groups for glare-free illumination if interior and exterior spaces.

Materials
Luminaire housing constructed marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Three-ply opal glass
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 12.2lbs

Electrical
Operating voltage120-277V AC
Minimum start temperature-30° C
LED module wattage28.1 W
System wattage32.0 W
Controllability0-10V dimmable
Color rendering indexRa > 90
Luminaire lumens2,601 lumens (3000K)
Lifetime at Ta = 15° C487,000 h (L70)
Lifetime at Ta = 35° C142,000 h (L70)


LED color temperature
4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :

Type:
BEGA Product:
Project:
Modified:



LED ceiling and wall luminaire · unshielded			
	LED	A	B
24 223	28.1 W	18 1⁄8	4 3⁄4

