


# BEGA

Photometric Filename: 24223.IES

TEST: BE\_24223  
TEST LAB: BEGA  
DATE: 1/4/2017  
LUMINAIRE: 24 223  
LAMP: 28.1W LED




## Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2601
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	81
Total Luminaire Watts	32
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.40
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	1.50 ft (Diameter)
Luminous Height	0.26 ft

## Zonal Lumen Summary

Zone	Lumens
0-10	70.83
10-20	203.21
20-30	309.14
30-40	375.08
40-50	392.15
50-60	357.49
60-70	277.09
70-80	172.98
80-90	84.21
90-100	39.86
100-110	34.79
110-120	43.54
120-130	50.97
130-140	54.57
140-150	53.06
150-160	45.02
160-170	29.14
170-180	7.74



Ceiling Mount - Isofootcandle Grid on Floor  
Mounting Height = 10 ft. Grid Spacing = 10 ft.



Wall Mount - Isofootcandle Grid on Floor  
Mounting Height = 10 ft. Grid Spacing = 10 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

**BEGA** 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 [www.bega-us.com](http://www.bega-us.com) © Copyright BEGA-US 2018

5/15/2018