


BEGA

Photometric Filename: 24226.IES

TEST: BE_24226
TEST LAB: BEGA
DATE: 2/17/2017
LUMINAIRE: 24 226
LAMP: 15.6W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1785
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	94
Total Luminaire Watts	19
Ballast Factor	1.00
CIE Type	Semi-Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.40
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	1.08 ft (Diameter)
Luminous Height	0.23 ft

Zonal Lumen Summary

Zone	Lumens
0-10	48.00
10-20	137.70
20-30	209.49
30-40	254.35
40-50	266.79
50-60	246.04
60-70	197.64
70-80	134.29
80-90	75.81
90-100	38.86
100-110	25.02
110-120	24.40
120-130	27.22
130-140	29.08
140-150	28.07
150-160	23.60
160-170	15.55
170-180	3.58



Ceiling Mount - Isofootcandle Grid on Floor
Mounting Height = 10 ft. Grid Spacing = 10 ft.



Wall Mount - Isofootcandle Grid on Floor
Mounting Height = 10 ft. Grid Spacing = 10 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

5/14/2018