

Application

LED ceiling and wall luminaires with impact-resistant polyethylene diffuser. The impact-resistant diffuser adds strength and security in locations where glass cannot be used. This luminaire can be utilized individually or in groups for glare-free illumination if interior and exterior spaces.

Materials

Luminaire housing constructed marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
White high density polyethylene diffuser
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 4.0lbs

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 15.6 W
System wattage 19.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 90
Luminaire lumens 1,785 lumens (3000K)
Lifetime at Ta = 15° C 310,000 h (L70)
Lifetime at Ta = 35° C 190,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:
BEGA Product:
Project:
Modified:



LED ceiling and wall luminaire · unshielded			
	LED	A	B
24 226	15.6 W	13	4 1/8

