

**Application**

LED linear ceiling and wall luminaire with unshielded light distribution. Arranged individually, in continuous bands of light or grouped together, these luminaires can accentuate building architecture while providing glare free illumination.

**Materials**

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 White safety glass  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65  
 Weight: 11.9lbs

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -20° C  
 LED module wattage 32.0W  
 System wattage 36.0W  
 Controllability 0-10V dimming down to 0.1%  
 Color rendering index Ra > 80  
 Luminaire lumens 2,038 lumens (3000K)  
 LED service life (L70) 60,000 hours

**LED color temperature**

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors    Black (BLK)            White (WHT)            RAL:  
                               Bronze (BRZ)            Silver (SLV)            CUS:



LED linear ceiling and wall luminaire · unshielded					Required wiring box
	LED	A	B	C	
<b>24319</b>	<b>ADA</b> 32.0W	40	2 3/8	3 3/4	<b>19537</b>

Type:  
 BEGA Product:  
 Project:  
 Modified:

