

Application

LED linear ceiling and wall luminaire with unshielded light distribution. Arranged individually, in continuous bands of light or grouped together, these luminaires can accentuate building architecture while providing glare free illumination.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 White safety glass
 Silicone applied robotically to casting, plasma treated for increased adhesion
 High temperature silicone gasket
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65
 Weight: 20.1 lbs

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -40° C
 LED module wattage 48.0 W
 System wattage 55.0 W
 Controllability 0-10V dimming
 Color rendering index Ra > 80
 Luminaire lumens 3,359 lumens (3000K)
 LED service life (L70) 60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) White (WHT) RAL:
 Bronze (BRZ) Silver (SLV) CUS:



LED linear ceiling and wall luminaire · unshielded

	LED	A	B	C
24 320	ADA 48.0W	59 ¼"	2 ¾"	3 ¾"

