

Application

LED wall washer luminaires with symmetrical light distribution designed for illuminating wall surfaces, with the mounting surface also acting as the reflection surface.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Clear safety glass
Reflector made of pure anodized aluminum
Silicone applied robotically to casting, plasma treated for increased adhesion
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 5.8lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	33.6 W
System wattage	38.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	3,978 lumens (3000K)
Lifetime at Ta = 15° C	217,000 h (L70)
Lifetime at Ta = 40° C	53,000 h (L70)

LED color temperature


4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



LED wall washer · symmetrical light distribution				
	LED	A	B	C
24 361	33.6 W	12 5/8	4 1/4	6

Type:

BEGA Product:

Project:

Modified:

