

**Application**

LED wall mounted luminaires with directed light designed to be mounted at various heights for general purpose illumination or glare free illumination when below eye level.

**Materials**

Luminaire housing constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Matte safety glass  
 Silicone applied robotically to casting, plasma treated for increased adhesion  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP65  
 Weight: 3.6lbs

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	12.3W
System wattage	15.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	1,077 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 45° C	108,000 h (L70)

**LED color temperature**


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



**LED wall luminaires - directed**

	LED	A	B	C
<b>24374</b>	<b>ADA</b> 12.3W	11 7/8"	4 3/8"	3 3/8"

Type:  
 BEGA Product:  
 Project:  
 Modified:

