

# LED pendant luminaire - shielded light

**Application**

LED pendant luminaire with shielded, downward directed light distribution ideal for down lighting atria, passages and other large covered spaces.

**Materials**

- Luminaire housing and canopy constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy
- Clear safety glass
- Reflector made of pure anodized aluminum
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Black power cable
- Steel suspension wires

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP65  
 Weight: 12.4 lbs

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	35.7 W
System wattage	40.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	4,107 lumens (3000K)
Lifetime at Ta = 15° C	> 500,000 h (L70)
Lifetime at Ta = 30° C	312,000 h (L70)

**LED color temperature**


- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED pendant · shielded					
	LED	A	B	C	Wiring Box*
<b>24507</b>	35.7W	7 1/2	17 1/4	103 1/2	<b>19538</b>

\*Small opening wiring box included

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Type:  
 BEGA Product:  
 Project:  
 Modified:

