


BEGA

Photometric Filename: 24590.ies

TEST: BE_24590
TEST LAB: BEGA
DATE: 2/6/2017
LUMINAIRE: 24 590
LAMP: 15.6W LED




Characteristics

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1538
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	77
Total Luminaire Watts	20
Ballast Factor	1.00
CIE Type	General Diffuse
Spacing Criterion (0-180)	N.A.
Spacing Criterion (90-270)	N.A.
Spacing Criterion (Diagonal)	N.A.
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.26 ft (Diameter)
Luminous Height	1.63 ft

Zonal Lumen Summary

Zone	Lumens
0-10	0.82
10-20	8.43
20-30	26.40
30-40	52.69
40-50	83.59
50-60	115.05
60-70	143.08
70-80	164.00
80-90	174.70
90-100	174.70
100-110	164.00
110-120	143.08
120-130	115.05
130-140	83.59
140-150	52.69
150-160	26.40
160-170	8.43
170-180	0.82



Ceiling Mount - Isofootcandle grid on floor
Mounting Height = 10 ft. Grid Spacing = 8 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

2/14/2018