

Application

LED wall luminaires with unshielded light distribution. The linear shape of these luminaires makes them particularly suitable for installation on columns, walls and pillars. These luminaires can be installed vertically or horizontally.

Materials

Luminaire housing and faceplate constructed of die-cast and extruded marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Three-ply opal glass
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 6.2lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	19.6 W
System wattage	23.8 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1,770 lumens (3000K)
Lifetime at Ta=15° C	360,000 h (L70)
Lifetime at Ta=40° C	82,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS :



LED wall luminaires - unshielded					Required wiring box
	LED	A	B	C	
24 591	19.6 W	3 ⅞	23 ⅝	4 ½	19537

Type:
BEGA Product:
Project:
Modified:

