


Tools Required:

- 3mm hex key
- Phillips medium screwdriver
- Adjustable wrench



Dimensions

- A: 8-7/8"
- B: 4-1/8"
- C: 19-1/8"
- D: 5-1/8"



Protection Class: IP65


Weight: 11.5 lb.

Notice to Installer for 24 816:

1. BEGA luminaires may be damaged if connected to conduit systems containing water - Article 300-5G of National Electric Code requires that "Conduits or raceways through which moisture may contact energized live parts shall be sealed or plugged at either or both ends".
2. Luminaire mounts directly to recessed 4" octagonal J-box (by others).
3. It is the installing contractor's responsibility to ensure that J-box be adequately supported, and maximum load requirements be adhered to, as per code requirements.
4. Suitable for any mounting orientation.

24 816 - installation:

1. Loosen (2) 3mm hex head screws to remove mounting canopy base.
2. Route luminaire wires through canopy base and into wiring box.
3. Make supply wiring and luminaire wiring connections inside the wiring box:
MAIN VOLTAGE SUPPLY WIRE TO BLACK LUMINAIRE WIRE
NEUTRAL (COMMON) SUPPLY WIRE TO WHITE LUMINAIRE WIRE
GREEN GROUND WIRE TO GREEN LUMINAIRE WIRE.
Dimming (if applicable):
DIMMING CONTROL WIRE (+) TO POSITIVE LUMINAIRE DIM CONTROL WIRE
DIMMING CONTROL WIRE (-) TO NEGATIVE LUMINAIRE DIM CONTROL WIRE
4. Mount luminaire canopy to J-box using hardware by others (minimum size 8-32).
5. Slip fixture over canopy base and tighten (2) 3mm hex head screws to secure.
6. To adjust tilt angle, loosen hex nut at fixture arm joint and adjust to desired angle. Re-tighten hex nut to lock into place.



IMPORTANT NOTE:

In conformance with U.L. Standards 1598, a silicone-based sealant MUST be used between the mounting plate edge and supporting wall.

Cleaning/Maintenance

Undo faceplate screws and remove casting. Carefully remove lens frame with attached gasket. Clean luminaire and lens using only solvent-free cleansers. Replace lens and casting, making sure that the gasket is seated properly.

Accessories

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

Replacement Parts

Description	Part No
Faceplate Assembly	FP66851
Driver (120-277V)	76084-1050
LED Module (3000K)	LED-0773/830
LED Module (4000K)	LED-0773/840

Lamp: 55.3W LED

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

Product Safety Warnings:

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED. SUITABLE FOR WET LOCATIONS.

MIN 60°C SUPPLY CONDUCTORS.

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS. CONVIENT AUX EMPLACEMENTS MOUILLÉS.

LES FILS D'ALIMENTATION 60°C MIN.
