


BEGA

Photometric Filename: 24828.ies

TEST: BE_24828
TEST LAB: BEGA
DATE: 4/28/2017
LUMINAIRE: 24 828
LAMP: 35.7W LED




Characteristics


NEMA Type	4 H x 4 V
Maximum Candela	11686.8
Maximum Candela Angle	0 H 0 V
Horizontal Beam Angle (50%)	31.7
Vertical Beam Angle (50%)	31.7
Horizontal Field Angle (10%)	65.2
Vertical Field Angle (10%)	65.2
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	2118
Beam Efficiency	N.A.
Field Lumens	4121
Field Efficiency	N.A.
Spill Lumens	469
Luminaire Lumens	4591
Total Efficiency	N.A.
Total Luminaire Watts	40

Zonal Lumen Summary

Zone	Lumens
0-10	1036.11
10-20	1758.35
20-30	1115.3
30-40	510.52
40-50	120.39
50-60	43.49
60-70	2.29
70-80	0.00
80-90	0.00
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mouting Height = 20 ft. Grid Spacing = 10 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

1/17/2018