


BEGA

Photometric Filename: 24833.ies

TEST: BE_24833
TEST LAB: BEGA
DATE: 6/7/2017
LUMINAIRE: 24 833
LAMP: 24.1W LED




Characteristics


| | |
|------------------------------|-----------------|
| NEMA Type | 5 H x 5 V |
| Maximum Candela | 3489.3 |
| Maximum Candela Angle | -7 H -7 V |
| Horizontal Beam Angle (50%) | 56.5 |
| Vertical Beam Angle (50%) | 56.5 |
| Horizontal Field Angle (10%) | 79.9 |
| Vertical Field Angle (10%) | 79.9 |
| Lumens Per Lamp | N.A. (absolute) |
| Total Lamp Lumens | N.A. (absolute) |
| Beam Lumens | 2265 |
| Beam Efficiency | N.A. |
| Field Lumens | 2835 |
| Field Efficiency | N.A. |
| Spill Lumens | 215 |
| Luminaire Lumens | 3050 |
| Total Efficiency | N.A. |
| Total Luminaire Watts | 28 |

Zonal Lumen Summary

| Zone | Lumens |
|---------|---------|
| 0-10 | 329.33 |
| 10-20 | 939.16 |
| 20-30 | 1081.58 |
| 30-40 | 484.59 |
| 40-50 | 152.72 |
| 50-60 | 44.06 |
| 60-70 | 7.89 |
| 70-80 | 0.23 |
| 80-90 | 0.00 |
| 90-100 | 0.00 |
| 100-110 | 0.00 |
| 110-120 | 0.00 |
| 120-130 | 0.00 |
| 130-140 | 0.00 |
| 140-150 | 0.00 |
| 150-160 | 0.00 |
| 160-170 | 0.00 |
| 170-180 | 0.00 |



Mouting Height = 15 ft. Grid Spacing = 10 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

1/17/2018