

LED wall luminaire with directed light

Material: Luminaire housing constructed of aluminum. Luminaire shade constructed of aluminum with inside white painted finish. Housing secured to stainless steel mounting plate with stainless steel set screw. Designed for installation directly to a standard 4" octagonal wiring box.

Glass: Hand-blown, three-ply opal glass with screw neck.

Electrical: 6.3W LED luminaire, 8 total system watts, -20°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.


Finish: BEGA standard finish is polyester powder coat with minimum 3 mil thickness. Available in BEGA Black (BLK).

CSA certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP44

Weight: 3.3 lbs

Luminaire Lumens: 394

Type:
BEGA Product:
Project:
Voltage:
Color:
Options:
Modified:



| Lamp | | A | B | C | D |
|--------|-----------|------|------|----|-----|
| 31 016 | 6.3 W LED | 10 ¼ | 10 ¼ | 13 | 4 ¾ |