

LED wall luminaire with half lid - tool-less entry - Shielded light

Material: Luminaire housing constructed of cast bronze with brass hinge and thumb screws. Designed for installation directly to a standard 4" octagonal wiring box using adapter plate.

Glass: Crystal glass with light diffusing texture, inside white.

Electrical: 7.9W LED luminaire, 10 total system watts, -20°C start temperature. Integral 120V-277V electronic LED driver, 0-10V, TRIAC and ELV dimmable. LED module(s) are available from factory for easy replacement. LED color temperature is 3000K with a >80 CRI.

Note: LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to www.bega-us.com.


Finish: Natural cast bronze finish. Time and weather factors will create the natural patina of bronze.

CSA certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

Weight: 16 lbs

Luminaire Lumens: 257

Type:
 BEGA Product:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



Wall luminaires - Access **without** a tool

| | Lamp | A | B | C |
|---------------|-----------|--------------------------------|--------------------------------|-------------------------------|
| 31 148 | 7.9 W LED | 10 ⁷ / ₈ | 10 ¹ / ₄ | 5 ¹ / ₄ |