

Application

LED recessed wall luminaire with asymmetrical wide spread light distribution for the illumination of wide ground surfaces, stairs and footpaths.

Materials

Luminaire housing constructed of die-cast aluminum marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Clear safety glass
Reflector made of pure anodized aluminum
Silicone applied robotically to casting, plasma treated for increased adhesion
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Stainless steel screw clamps
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP65
Weight: 1.9 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40°C
LED module wattage	5.8W
System wattage	8.0W
Controlability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	463 lumens (3000K)
Lifetime at Ta=15°C	> 500,000 h (L70)
Lifetime at Ta=30°C	226,000 h (L70)

LED color temperature

2700K - Product number + **K27**
3000K - Product number + **K3**
3500K - Product number + **K35**
4000K - Product number + **K4**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:
BEGA Product:
Project:
Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.



LED recessed wall luminaires · asym. wide spread				
	LED	A	B	C
33046	5.8 W	10 1/8	2 3/4	5