

Application

LED recessed wall luminaire with asymmetrical wide spread light distribution for the illumination of wide ground surfaces, stairs and footpaths.

Materials

- Luminaire housing constructed of die-cast aluminum marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
- Clear safety glass
- Reflector made of pure anodized aluminum
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP65
Weight: 2.9 lbs

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-40°C
- LED module wattage8.2W
- System wattage11.0W
- Controlability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens621 lumens (3000K)
- Lifetime at Ta=15°C420,000 h (L70)
- Lifetime at Ta=35°C125,000 h (L70)

LED color temperature

- 2700K - Product number + **K27**
- 3000K - Product number + **K3**
- 3500K - Product number + **K35**
- 4000K - Product number + **K4**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

- | | | | |
|------------------|--------------|--------------|------|
| Available colors | Black (BLK) | White (WHT) | RAL: |
| | Bronze (BRZ) | Silver (SLV) | CUS: |

Type:
BEGA Product:
Project:
Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.



LED recessed wall luminaires · asym. wide spread				
	LED	A	B	C
33049	8.2W	12 1/2	2 3/4	5