

Application

LED recessed wall luminaire with asymmetrical light distribution for the illumination of ground surfaces, building entrances, stairs and footpaths.

Materials

- Luminaire housing constructed of die-cast aluminum marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Clear safety glass
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP65  
Weight: 2.1 lbs

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-40° C
- LED module wattage8.4 W
- System wattage11.0 W
- Controlability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens480 lumens (3000K)
- LED service life (L70)60,000 hours

LED color temperature

- 4000K - Product number + **K4**
- 3500K - Product number + **K35**
- 3000K - Product number + **K3**
- 2700K - Product number + **K27**
- Amber - Product number + **AMB**

Wildlife friendly amber LED - Optional

Luminaire is optionally available with a narrow bandwidth, amber LED source (585-600nm) approved by the FWC. This light output is suggested for use within close proximity to sea turtle nesting and hatching habitats. Electrical and control information may vary from standard luminaire.


- LED module wattage8.7 W (Amber)
- System wattage10.7 (Amber)
- Luminaire lumens111 lumens (Amber)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

- |                  |              |              |      |
|------------------|--------------|--------------|------|
| Available colors | Black (BLK)  | White (WHT)  | RAL: |
|                  | Bronze (BRZ) | Silver (SLV) | CUS: |



LED recessed wall luminaires · asymmetrical				
	LED	A	B	C
33055	8.4 W	12 ½	2 ¾	5

Type:  
BEGA Product:  
Project:  
Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.

