

Application

LED recessed wall luminaire with asymmetrical light distribution for the illumination of ground surfaces, building entrances, stairs and footpaths.

Materials

- Luminaire housing constructed of die-cast aluminum marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Clear safety glass
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP65
Weight: 5.3 lbs

Electrical

| | |
|---------------------------|----------------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -30° C |
| LED module wattage | 16.4 W |
| System wattage | 20.0 W |
| Controlability | 0-10V |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 1,486 lumens (3000K) |
| Lifetime at Ta=15°C | 198,000 h (L70) |
| Lifetime at Ta=30°C | 84,000 h (L70) |

LED color temperature

- 2700K - Product number + **K27**
- 3000K - Product number + **K3**
- 3500K - Product number + **K35**
- 4000K - Product number + **K4**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

| | | | |
|------------------|--------------|--------------|-------|
| Available colors | Black (BLK) | White (WHT) | RAL: |
| | Bronze (BRZ) | Silver (SLV) | CUS : |

Type:
BEGA Product:
Project:
Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.



| LED recessed wall luminaires · asymmetrical | | | | |
|---|--------|------|---|-----|
| | LED | A | B | C |
| 33059 | 16.4 W | 16 ½ | 5 | 5 ½ |