


# BEGA

Photometric Filename: 33067.ies

TEST: BE\_33067  
TEST LAB: BEGA  
DATE: 8/11/2015  
LUMINAIRE: 33 067  
LAMP: 16.8W LED




## Characteristics

IES Classification	Type IV
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1470
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	73
Total Luminaire Watts	20
Ballast Factor	1.00
Upward Waste Light Ratio	0.10
Max. Cd.	1020.7 (15H, 62.5V)
Max. Cd. (<90 Vert.)	1020.7 (15H, 62.5V)
Max. Cd. (At 90 Deg. Vert.)	184.5 (12.6%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	362.3 (24.6%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


## Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	78.1	N.A.	5.3
FM (30-60)	593.2	N.A.	40.4
FH (60-80)	563.0	N.A.	38.3
FVH(80-90)	92.3	N.A.	6.3
BL (0-30)	< 0.05	N.A.	0.0
BM (30-60)	0.1	N.A.	0.0
BH (60-80)	< 0.05	N.A.	0.0
BVH(80-90)	< 0.05	N.A.	0.0
UL (90-100)	63.5	N.A.	4.3
UH (100-180)	79.4	N.A.	5.4
Total	1469.6	N.A.	100.0

**BUG Rating B0-U3-G1**



Mounting Height = 2 ft. Grid Spacing = 4 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

1/23/2018