

Application

LED recessed wall luminaire with unshielded light for use as location luminaires for means of way finding.

Materials

Floodlight housing constructed of die-cast aluminum marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
White safety glass
Silicone applied robotically to plasma treated casting for increased adhesion
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Stainless steel screw clamps
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP65
Weight: 1.2 lbs

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30°C
LED module wattage	2.0W
System wattage	3.0W
Controlability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	150 lumens (3000K)
Lifetime at Ta=15°C	105,000 h (L70)
Lifetime at Ta=40°C	72,000 h (L70)

LED color temperature

2700K - Product number + **K27**
3000K - Product number + **K3**
3500K - Product number + **K35**
4000K - Product number + **K4**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish



All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:
BEGA Product:
Project:
Modified:



Fully enclosed luminaire with installation housing ensures seamless integration and weathertight operation.



LED recessed wall luminaires · unshielded location luminaires				
	LED	A	B	C
33 107	2.0W	6 5/8	2 3/4	5