

LED wall washer with asymmetrical light distribution

**Housing:** One piece die-cast aluminum designed for direct attachment to wall over a horizontally oriented recessed single gang junction box. Die castings are marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy.

**Enclosure:** Tempered clear glass, retained by one piece die-cast aluminum frame attached to housing with two (2) stainless steel captive set screws threaded into stainless steel inserts. Reflector made of pure anodized aluminum. Fully gasketed for weather tight operation using molded silicone gasket.

**Electrical:** 16.5W LED luminaire, 19.5 total system watts,  $-30^{\circ}\text{C}$  start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 3000K with an 85 CRI. Available in 4000K (85 CRI); add suffix K4 to order.



**Note:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

**CSA** certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

**Weight:** 3.5 lbs

Type:  
BEGA Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:



Asymmetrical light distribution					
Lamp			A	B	C
33361	16.5W	LED	10 1/4	3	6