

Tools Required:

4mm hex key
Phillips medium screwdriver



Dimensions

A: 10-1/4 "
B: 5 "
C: 4-1/2 "



Protected Class: IP65

Weight: 5.1 lbs.

Notice to Installer for 33 371:

1. See page 2 for specific product safety warnings.
2. Mounts directly to standard recessed 4" octagonal wiring box (by others) using mounting strap provided.
3. A silicone based sealant must be used between luminaire and supporting wall.

WARNING: LEDs are high quality electrical components. Please avoid touching them directly during installation.

33 371 - Installation:


1. Loosen (4) screws on trim casting and remove lens from luminaire base, carefully.
2. Feed luminaire wires through hex nut, lock washer, luminaire base, I.P. nipple, and mounting strap provided.
3. Make supply wiring and luminaire wiring connections in the octagonal wiring box:
MAIN VOLTAGE SUPPLY WIRE TO BLACK LUMINAIRE WIRE
NEUTRAL (COMMON) SUPPLY WIRE TO WHITE LUMINAIRE WIRE
WIRE GREEN GROUND WIRE TO GREEN LUMINAIRE WIRE

Dimming (if applicable):

DIMMING CONTROL WIRE (+) TO POSITIVE DRIVER DIM CONTROL WIRE
DIMMING CONTROL WIRE (-) TO NEGATIVE DRIVER DIM CONTROL WIRE

4. Attach mounting strap to octagonal wiring box with hardware (by others).
5. Slip luminaire base over 1/4" I.P. nipple attached to mounting strap (see figure 1).
NOTE: Refer to orientation arrow on mounting base for proper orientation.
6. Place a small bead of silicone around the back side of the luminaire base that will come in contact with the finished wall (exterior applications only).
7. Secure luminaire base to mounting strap by using lock washer and hex nut provided.
8. Replace lens. Tighten (4) screws to secure.

Figure 1



Relamping/Maintenance

Loosen (4) screws on trim casting and remove lens.
Clean luminaire and lens using only solvent-free cleansers. Replace lens and tighten (4) screws.

Accessories

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

Replacement Parts

Description	Part No
Lens	11281011
Lens gasket	831152
Driver	75939
LED Module (3000K)	LED-0262/830
LED Module (4000K)	LED-0262/840

Lamp: 8.4W LED Module

Product Safety Warnings:

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED. SUITABLE FOR WET LOCATIONS.

MIN 90°C SUPPLY CONDUCTORS.

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS. CONVIENT AUX EMPLACEMENTS MOUILLÉS.

LES FILS D'ALIMENTATION 90°C MIN.