

Application

This LED wall luminaire has a symmetric light distribution on one side and a wide spread light distribution on the other side. The symmetric light distribution can be used to illuminate facade and wall surfaces, with the installation surface also acting as the reflection surface. The wide spread light distribution can be used to illuminate ground surfaces along walls.

Materials

Luminaire housing constructed of die-cast marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
Clear safety glass  
Reflector made of pure anodized aluminum  
Silicone applied robotically to casting, plasma treated for increased adhesion  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
Weight: 16.3lbs

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	70 W
System wattage	80 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	8963 lumens (3000K)
Lifetime at Ta = 15° C	50,000 h (L70)

LED color temperature


4000K - Product number + **K4**  
3500K - Product number + **K35**  
3000K - Product number + **K3**  
2700K - Product number + **K27**

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:



LED wall luminaire · light output on two sides				
	LED	A	B	C
33 379	70 W	12 7/8	7 1/8	8 5/8

Type:  
BEGA Product:  
Project:  
Modified:

